


# Model WS10EX with analog output Dust explosion-proof



## Compact sensor for dust explosive areas

- Protection class IP65
- Measurement ranges:  
0 ... 100 mm to 0 ... 1250 mm
- Analog output 0 ... 10 V, 4 ... 20 mA
- Dust ex proof, category 3, zone 22
- II 3D EEx T95°C IP65



Specifications	Outputs	Potentiometer: 1 kΩ Voltage: 0...10 V Current: 4...20 mA, 2 or 3 wire
	Material	Aluminium and stainless steel. Cable: stainless steel
Resolution	Essentially infinite	
Sensing Device	Precision potentiometer	
Connection	Cable output, standard length 1.5 m	
Linearity	Up to ±0.05 % full scale	
Weight	800 g max.	
Temperature	-20 to +70°C	
Conformity of standards		
	Explosion-proof	DIN EN 50281:1999, category 3, zone 22
	EMC	DIN EN 61326:2004
	Protection class of housing	DIN EN 60529:2000, IP65
	Shock	DIN EN 60068-2-27:1993, 50 g 11 ms, 100 shocks
	Vibration	DIN-EN 60068-2-6:1996, 20 g, 10 Hz ... 2 kHz, 10 cycles

Order Code WS10EX	Model Name
Analogue	WS10EX - [ ] - [ ] - [ ] - [ ] - [ ]
	<b>Measurement Range (in mm)</b> 100 / 125 / 375 / 500 / 750 / 1000 / 1250
	<b>Outputs</b> (see pages 57 and 58) R1K = Potentiometer 1 kΩ (other values on request) 10V = with 0 ... 10 V signal conditioner 420A = with 4 ... 20 mA signal conditioner (2 wire) 420T = with 4 ... 20 mA signal conditioner (3 wire)
	<b>Linearity</b> L10 = ±0.10 %    option:    L05 = ±0,05 %    L25 = ±0.25 %
	<b>Connection</b> KAB1,5M = Cable output, standard length 1.5 m
	<b>Cable fixing</b> M4 = M4 cable fixing SB0 = Cable clip


**Order Example: WS10EX - 1250 - 10V - L10 - KAB1,5M - M4**

# Model WS10EX with analog output Dust explosion-proof



Cable Forces typical at 20 °C	Range	Maximum pull-out Force	Minimum pull-in Force
	mm	[N]	[N]
	100	4.7	3.0
	125	4.6	2.4
	375	7.4	3.9
	500	5.5	2.8
	750	7.6	3.8
	1000	5.3	2.9
	1250	4.6	2.4

## Outline drawing




Dimensions informative only.  
For guaranteed dimensions consult factory

Dimensions	Range	A	B, C	E
	[mm]			
	375, 750	12,5		
	100, 125, 500	8,0	B=31; C=38,5	120,5
	1000, 1250	8,0		


# Output Specifications

## R1K and 10V for WS position sensors




<b>Voltage divider R1K</b> Potentiometer 	Excitation Voltage	32 VDC max. at 1 k $\Omega$ (input power 1 W max.)
	Potentiometer Impedance	1 k $\Omega$ $\pm$ 10%
	Thermal coefficient	$\pm$ 25 x 10 <sup>-6</sup> / °C full scale
	Sensitivity	Depends on measurement range, individual sensitivity of sensor specified on label
	Voltage Divider Utilization Range	Approx. 3% ... 97% of full range
	Operating Temperature	-20 ... +85 °C


### Signal diagram



Note: The potentiometer must be connected as a voltage divider. The input impedance of the following processing circuit should be 10 M $\Omega$  min.

<b>Signal conditioner 10V</b> Voltage output 	Excitation Voltage	+18 ... +27 V DC non stabilized
	Excitation Current	20 mA max.
	Output Voltage	0 ... +10 V DC
	Output Current	2 mA max.
	Output Load	> 5 k $\Omega$
	Stability (Temperature)	$\pm$ 50 x 10 <sup>-6</sup> / °C full scale
	Protection	Reverse polarity, short circuit
	Output Noise	0,5 mV <sub>RMS</sub>
	Operating Temperature	-20 ... +85 °C
EMC	According to EN 61326:2004	

### Signal diagram




Signal Wiring	Output signals		Cable color	Connector pin no.
	R1K	10V		
+ Vin		Excitation +	White	1
GND		Excitation GND	Brown	2
+ Vout		Signal +	Green	3
		Signal GND	Yellow	4


### Connection

#### Mating Connector

View to solder terminals



CONN-DIN-8F-W




CONN-M12-8F-G


# Output Specifications


## 420A and 420T for WS position sensors




<b>Signal conditioner</b> <b>420A</b> Current output (2 wire) 	Excitation Voltage	+12 ... 27 VDC non stabilized, measured at the sensor terminals
	Excitation Current	35 mA max.
	Output Current	4 ... 20 mA equivalent to 0 ... 100% range
	Stability (Temperature)	$\pm 100 \times 10^{-6} / ^\circ\text{C}$ full scale
	Protection	Reverse polarity, short circuit
	Output Noise	0.5 mV <sub>RMS</sub>
	Operating Temperature	-20 ... +85 °C
	EMC	According to EN 61326:2004

### Signal Diagram



<b>Signal Conditioner</b> <b>420T</b> Current output (3 wire) 	Excitation Voltage	+18...+27 V DC non stabilized
	Excitation Current	40 mA max.
	Load Resistor	350 Ω max.
	Output Current	4 ... 20 mA equivalent to 0 ... 100% range
	Stability (Temperature)	$\pm 50 \times 10^{-6} / ^\circ\text{C}$ full scale
	Protection	Reverse polarity, short circuit
	Output Noise	0.5 mV <sub>RMS</sub>
	Operating Temperature	-20 ... +85 °C
	EMC	According to EN 61326:2004


### Signal diagram



Signal Wiring	Output signals		Cable color	Connector pin no.
	420A	420T		
	Signal +	Excitation +	White	1
	Signal -	Excitation GND	Brown	2
		Signal +	Green	3

### Connection



Mating Connector




# Output Specification

## PMU for WS position sensors



<b>Signal Conditioner PMU, adjustable</b> Voltage output and current output (3 wire)    	Excitation voltage	+18 ... 27 V DC
	Excitation current	50 mA max.
	Voltage output	0 ... 10 V
	Output current	10 mA max.
	Output load	1 kΩ min.
	Current output	4 ... 20 mA (3 wire)
	Load resistor	500 Ω max.
	Adjustment	
	Activation of offset and gain adjust	Connect with excitation GND (0 V)
	Scalable range	90 % max. full scale
	Stability (Temperature)	$\pm 50 \times 10^{-6} / ^\circ\text{C}$ full scale
	Protection	Reverse polarity, short circuit
	Output noise	1 mV <sub>eff</sub>
Operating temperature	-20 ... +85 °C	
EMC	According to EN 61326:2004	

### Signal diagram



Signal wiring	Output signals	Connector pin no.
	Excitation +	1
	Excitation GND	2
	Signal 0...10 V +	3
	Signal 0...10 V GND	4
	Signal 4...20 mA +	5
	Signal 4...20 mA GND	6
	Offset	7
	Gain	8

### Connection

Mating Connector

